

SATIN SAFETY DATA SHEET



SECTION 1 - Indentification

Product identifier

Product name : XPEL FUSION PLUS SATIN

Product code : R1452 SDS # : XPEL-032

Recommended use of the chemical and restrictions on use

Surfactant. Protectant

Details of the supplier of the safety data sheet

XPEL, Inc. 3251 I-35

San Antonio, TX, 78219 T: +1 210-678-3700

Emergency telephone number

Emergency Number : +1 800-535-5053 (INFOTRAC)

: +1 352-323-3500 (INFOTRAC International)

SECTION 2 - Hazard(s) identification

 Appearance Clear liquid
 Physical state liquid
 Odor Aromatic

Classification

Acute toxicity - Inhalation (Dusts/Mists) Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Germ cell mutagenicity Category 1B Carcinogenicity Category 1B Specific target organ toxicity (single exposure) Category 3 Aspiration toxicity Category 1 Flammable liquids Category 3

Signal word : Danger

Hazard statements : Hazard statements

Harmful if inhaled Causes skin irritation Causes serious eye irritation May cause genetic defects

May cause cancer

May be fatal if swallowed and enters airways

Flammable liquid and vapor

Hazard pictograms







Precautionary statements - Prevention : Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof equipment

Keep cool

Precautionary statements - Response : If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing



SAFETY DATA SHEET



SECTION 2 - Hazard(s) identification

Precautionary statements - Response : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

Precautionary statements - Storage : Store locked up

Store in a well-ventilated place. Keep container tightly closed
Dispose of contents/container to an approved waste disposal plant

Precautionary statements - Disposal : Dispose of contents/container to an approved water Contents - Dispose of contents - Dispose of

SECTION 3 - Composition/Information on ingredients

Substances

Not applicable

SECTION 3 - Composition/Information on ingredients

Mixtures

| Name | CAS Number | Weight-% |
|-------------------------------------|------------|----------|
| Light aliphatic solvent naphtha | 64742-48-9 | 50-90 |
| t-Butyl Acetate | 540-88-5 | 0.1-5 |
| 1-chloro-4(trifluoromethyl) benzene | 98-56-6 | 0.1-3 |

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

SECTION 4 - First-aid measures

Description of first-aid measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

Skin Contact Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical

advice/attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If irritation persists, seek medical attention.

Ingestion Immediately call a poison center or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects (acute and delayed)

Symptoms Harmful if swallowed. May be harmful if swallowed. May be harmful in contact with skin. Causes skin irritation. Causes serious eye

irritation. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5 - Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined

Specific hazard arising from the chemical

Flammable liquid and vapor.

Explosion Data

Hazardous combustion products

Smoke, fumes or vapors, and oxides of carbon.

Sensitivity to Static Discharge

Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 - Accidental release measures

Personal precautions, protective equipment and emergency procedures

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Absorb with inert material or sweep up, and then place in suitable container for chemical waste.



SAFETY DATA SHEET



SECTION 7 - Handling and storage

Precautions for safe handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling.

(vacated) TWA: 2.5 mg/m3

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Incompatible Materials Strong oxidizers.

SECTION 8 - Exposure controls/personal protection

Control parameters

98-56-6

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------------------------|------------------------------|--|--|
| t-Butyl Acetate 540-88-5 | STEL: 150 ppm TWA: 50 ppm | TWA: 200 ppm TWA: 950 mg/m3 (vacated) TWA: 200 ppm (vacated) TWA: 950 mg/ m3 | IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m3 |
| 1-chloro-4(trifluoromethyl) benzene | TWA: 2.5 mg/m3 F | TWA: 2.5 mg/m3 F | IDLH: 250 mg/m3 F |

Appropriate Engineering Controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures/Personal protective equipment

Eye/Face Protection Wear eye/face protection. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Wear protective gloves and protective clothing. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection In case of insufficient ventilation, wear suitable respiratory equipment. Refer to 29 CFR 1910.134 for respiratory

protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Liquid Physical state Appearance Clear liquid Color Clear Odor Aromatic Odor Threshold Not determined No data available Melting point / freezing point No data available 48 °C / 118 °F Initial boiling point and boiling range 55 °C / 131 °F Flash point Evaporation Rate <1

Evaporation Rate <1

Flammability (Solid, Gas) Liquid-Not applicable

Flammability Limit in Air

Oxidizing Properties

Upper flammability or explosive limits No data available Lower flammability or explosive limits No data available Vapor Pressure Not determined Vapor Density No data available Relative Density Not determined Water Solubility Not determined Solubility in other solvents Not determined Partition Coefficient Not determined Autoignition temperature No data available Hyphen Not determined Kinematic viscosity 2 mm2/s Dynamic Viscosity Not determined **Explosive Properties** Not determined

Not determined



SATIN SAFETY DATA SHEET



SECTION 10: Stability and reactivity

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing

Conditions to avoid

Heat, flames and sparks. Direct sunlight. Incompatible Materials

Incompatible materials

Strong oxidizers.

Hazardous decomposition products

None known based on information supplied.

SECTION 11: Toxicological information

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact May be harmful in contact with skin.

Inhalation Harmful if inhaled.

Ingestion May be harmful if swallowed.

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|----------------------|-------------------------|--------------------------|
| Light aliphatic solvent naphtha 64742-48-9 | > 6000 mg/kg (Rat) | > 5000 mg/kg (Rabbit) | > 8500 mg/m3 (Rat) 4 h |
| t-Butyl Acetate 540-88-5 | = 4100 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 9482 mg/m3 (Rat) 4 h |
| 1-chloro-4(trifluoromethyl) benzene 98-56-6 | = 13 g/kg (Rat) | > 3300 mg/kg (Rabbit) | = 33 mg/L (Rat) 4 h |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the

product as a whole has not been tested.

Chemical name ACGIH IARC NTP OSHA

1-chloro-4(trifluoromethyl) Group 2B X
benzene

egend

98-56-6

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT - single exposure May cause drowsiness or dizziness.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 Oral LD50
 4,255.20 mg/kg

 Dermal LD50
 3,269.60 mg/kg

 ATEmix (inhalation-dust/mist)
 189.60 mg/l



SAFETY DATA SHEET



SECTION 12: Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Fish Crustacea Chemical name Algae/aquatic plants Light aliphatic solvent naphtha LC50: =2200mg/L (96h, 64742-48-9 Pimephales promelas) LC50: 296 - 362mg/L (96h, t-Butyl Acetate 540-88-5 Pimephales promelas)

1-chloro-4(trifluoromethyl) benzene EC50: =3.68mg/L (48h, LC50: =3mg/L (96h, Danio rerio) 98-56-6 Daphnia magna)

Persistence and degradability

Not determined.

Bioaccumulative potential

There is no data for this product.

Mobility

Chemical name **Partition coefficient** t-Butyl Acetate 1.64 540-88-5 1-chloro-4(trifluoromethyl) benzene 3.70 98-56-6

Other adverse effects

Not determined.

SECTION 13: Disposal considerations

13.1 Disposal methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14: Transport information

Note Please see current shipping paper for most up to date shipping information, including exemptions and special

> circumstances Not regulated

DOT

According to 49 CFR \$173.150(f)(1), this material should be reclassified as "NA1993, Combustible Liquid, N.O.S." if it

is shipped in bulk

IATA

UN number or ID number UN1268

Proper Shipping Name Petroleum distillates, n.o.s.

Transport hazard class(es) 3 Packing group Ш

IMDG

UN number or ID number UN1268

Proper Shipping Name Petroleum distillates, n.o.s.

Transport hazard class(es) Packing Group Ш



SAFETY DATA SHEET



SECTION 15: Regulatory information

International Inventories

| Chemical name | TSCA | TSCA Inventory Status | DSL/NDSL | EINECS/ELINCS | ENCS | IECSC | KECL | PICCS | AIIC |
|--|------|--------------------------|----------|---------------|------|-------|------|-------|------|
| Light aliphatic solvent naphtha | X | ACTIVE | Χ | X | | Χ | Χ | Χ | Χ |
| Ambient curable resin mixture | X | ACTIVE | Χ | | | | | | X |
| t-Butyl Acetate | X | ACTIVE | Χ | X | × | Χ | Χ | Χ | Χ |
| 1-chloro-4(trifluoromethyl) benzene | Χ | ACTIVE | X | Χ | X | Χ | X | X | Χ |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|-----------------------------|--------------------------|----------------|--|
| t-Butyl Acetate 540-88-5 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|-----------------|-----------------------------|------------------------|---------------------------|-------------------------------|
| t-Butyl Acetate | | | | X |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

| Chemical name | Partition coefficient |
|---|-----------------------|
| 1-chloro-4(trifluoromethyl) benzene - 98-56-6 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|-------------------------------------|------------|---------------|--------------|
| t-Butyl Acetate 540-88-5 | X | X | Х |
| 1-chloro-4(trifluoromethyl) benzene | X | | |



SATIN SAFETY DATA SHEET



16. OTHER INFORMATION

NFPA

Health hazards Flammability Instability Special hazards

- - -

HMISHealth hazards Flammability Physical Hazards Personal Protection

- Not determined

Issue Date: 15-Feb-2023
Revision Date: 01-Apr-2023
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet